



## FLRY11Y

### Application:

Connection cable in cars and trucks with reduced wall thickness, e.g. for ABS systems.

### Standards/Specification:

ISO6722



### Construction:

- 1 Conductor: Soft-annealed electrolytic tinned copper Cu-ETP1 according to DIN EN 13602, bare conductor construction according to ISO 6722.
- 2 Insulation: PVC(Lead free)
- 3 Sheath: Polyurethane( PUR)



### Product Features:

Voltage rating: 60 V d.c, 25 V a.c.

Temperature range: -40 °C to +125 °C (3000 h)

### Technical Data:

Nominal Cross-Section (mm <sup>2</sup> )	Strand No./Max. Diameter (N/mm)	Diameter of Conductor (mm)	Nominal Insulation Thickness (mm)	Min. Sheath Thickness (mm)	Nominal Overall Diameter (mm)	Weight Approx. (kg/km)
3×0.75	19/0.23	1.2	0.30	0.58	5.6	45
4×0.5	19/0.19	1.0	0.28	0.58	5.4	40
4×1.5	19/0.32	1.7	0.30	0.7	7.6	96
5×1.5 +1×0.5	19/0.32	1.7	0.30	0.7	8.1	160
(0.5)	19/0.19	1.0	0.28			
2×4.0+1×2.5+3×1.5	56/0.30	2.60	0.40	0.75	10.2	205
(2.5)	19/0.40	2.05	0.35			
(1.5)	19/0.32	1.60	0.30			